




**INDUSTRIAL STAINLESS STEEL VALVES**  
**CLASS 200 STAINLESS GATE VALVE**



SCREWED BONNET, NRS, SCREWED END ASTM A 351  
CF8M, 200 PSI WORKING PRESSURE AT 350°

**DIMENSIONS**

SIZE	1/4		3/8		1/2		3/4		1		1-1/4		1-1/2		2		2-1/2		3	
	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm
L	1.97	50	1.97	50	2.17	55	2.36	60	2.56	65	3.15	80	3.35	85	3.74	95	4.33	110	4.92	125
H	3.54	90	3.54	90	3.74	95	4.33	110	4.72	120	5.31	135	5.71	145	6.69	170	8.27	210	9.25	235
D	0.43	11	0.43	11	0.59	15	0.79	20	0.98	25	1.26	32	1.50	38	1.97	50	2.56	65	3.15	80



MODEL: #907

**STANDARD**  
DESIGN: ANSI B16.34  
TESTING: API 598


**CLASS 200 STAINLESS GLOBE VALVE**



SCREWED BONNET, NRS, SCREWED END ASTM A 351  
CF8M, 200 PSI WORKING PRESSURE AT 350°

**DIMENSIONS**

SIZE	1/4		3/8		1/2		3/4		1		1-1/4		1-1/2		2	
	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm
L	1.97	50	1.97	50	2.17	55	2.44	62	2.95	75	3.15	80	3.54	90	4.13	105
H	2.95	75	2.95	75	2.95	75	3.35	85	3.54	90	3.94	100	4.53	115	4.72	120
D	0.39	10	0.39	10	0.39	10	0.59	15	0.79	20	0.98	25	1.26	32	1.50	38



MODEL: #908

**STANDARD**  
DESIGN: ANSI B16.34  
TESTING: API 598


**CLASS 200 STAINLESS SWING CHECK VALVE**



SCREWED BONNET, NRS, SCREWED END ASTM A 351  
CF8M, 200 PSI WORKING PRESSURE AT 350°

**DIMENSIONS**

SIZE	1/4		3/8		1/2		3/4		1		1-1/4		1-1/2		2		2-1/2		3	
	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm
L	2.36	60	2.36	60	2.56	65	3.19	81	3.54	90	4.13	105	4.72	120	5.51	140	7.09	180	7.87	200
H	1.65	42	1.65	42	1.89	48	2.17	55	2.44	62	2.76	70	3.15	80	3.54	90	4.53	115	4.92	125
D	0.43	11	0.43	11	0.59	15	0.79	20	0.98	25	1.26	32	1.50	38	1.97	50	2.56	65	3.15	80



MODEL: #909


**STANDARD**  
DESIGN: ANSI B16.34  
TESTING: API 598

**CLASS 600 STAINLESS "Y" STRAINER**



**DIMENSIONS**

SIZE	1/4		3/8		1/2		3/4		1		1-1/4		1-1/2		2		2-1/2		3	
	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm
L	0.35	9	0.35	9	0.55	14	0.67	17	0.87	22	1.06	27	1.34	34	1.65	42	2.40	61	2.99	76
H	2.64	67	2.64	67	2.99	76	3.43	87	4.06	103	4.72	120	5.31	135	6.30	160	7.87	200	8.86	225
D	1.65	42	1.65	42	1.99	50.6	2.21	56.2	2.73	69.3	3.13	79.5	3.65	92.6	4.24	107.8	5.28	134	5.72	145.3



MODEL: #910

**STANDARD**  
DESIGN: ANSI B16.34  
TESTING: API 598